



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:

GPWRB30

SERIES SPECIFICATIONS

RPP's GPWRB30 is a pre-grounded, pre-wired, NEMA 3R rainproof 30A generator power inlet box that allows you to safely power your home.

- Corrosion-resistant Powder-coated Steel Enclosure
- Compatible with NEMA L14-30C 30A, 120/240VAC Locking Connectors.
- This pre-wired, pre-grounded unit is ready to be directly spliced to field wiring.
- Compatible with Siemens HR series hubs.
- Featuring a spring-loaded bottom cover. This design provides effortless weather-resistant protection right where you need it.
- Must be used in conjunction with a transfer switch.



ELECTRICAL SPECIFICATIONS

Contact Configuration: 3-Pole, 4-Wire
Contact Rating: 30A
Rated Input Voltage Range: 120-240VAC

Short Circuit Protection: 5KA RMS Symmetrical Amps

CERTIFICATIONS

Construction Standard: NEMA 3R
File Number: 5027634
Performance Certifications: Weather Resistant
Safety Certifications: cETLus Listed

ENVIRONMENTAL SPECIFICATIONS

NEMA Rating: NEMA 3R
UL Location Rating: Wet Location

PHYSICAL SPECIFICATIONS

Conductor Material: Copper
Conductor Size: 10AWG
Connection: Pre-wired, pre-grounded; flying Leads
Construction Type: Metallic / Hinged Cover / Screw Down Cover
Finish Type: Powder Coated
Housing Material: Steel

Mounting: Hub mountable, Compatible with Siemens HR series of conduit hubs.
Number Of Conductors: 4-Wire
Number Of Poles: 3-Pole
Type: L14-30P



PROJECT:	
LOCATION:	
MODEL#:	TYPE:
CLIENT:	QTY:
PREPARED BY:	DATE:



WARRANTY INFORMATION

Warranty: 1 Year

WARNING SPECIFICATIONS

Warnings: Not for indoor use. Hazard of electrical shock or burn, turn off power before working inside this equipment.

SHIPPING SPECIFICATIONS

Case

Length: 6.75
QTY: 1

Weight: 3.5
Width: 4.25

Master Case

Height: 9
Length: 10