



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

## SERIES SPECIFICATIONS

20A 125V Duplex Receptacle, Back/Side Wired, Isolated Ground  
 Automatic grounding clip provides safe ground continuity between strap and metal enclosure  
 Side located grounding screw backed out and ready to wire  
 One-piece, triple-wipe brass line contacts for minimum heat rise, maximum plug retention  
 Break-off tabs for easy two-circuit conversion



## CONSTRUCTION

Color  
White

Grade  
Isolated Ground

Device Type  
Duplex Receptacle

Strap Material  
Steel

Environmental Rating  
Flammability UL94, V2 Rating

Operation Temperature  
From -40°C (without impact)  
to 75°C Maximum continuous

NEMA Configuration  
5-20R

## ELECTRICAL SPECIFICATIONS

Amperage  
20 Ampere

Voltage  
125 V AC

Poles  
2

Termination 1  
Back Wired #10 - #14 wire

Termination 2  
Side Wired, #12 AWG - #14  
AWG Cu Solid or Stranded  
wire

Grounding Capable  
Grounding

Wires  
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :			TYPE
PROJECT :			
PREPARED BY :		DATE :	

## CERTIFICATIONS/WARRANTY

Listing  
UL listed Listed

Warranty  
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

## ORDERING INFORMATION

Part Number: IGR20-WH

Box Qty : 10

Weight (Lbs) : 0.181

Carton Qty. : 100

IMS Code : 0288-1722

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM