



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 125V Duplex Receptacle, Side Wire, Commercial Grade
High-impact thermoplastic face and back is durable and long lasting, eliminating cracks and breaks
Captive mounting screws
Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)
Washer-type break off plaster ear for flush alignment



CONSTRUCTION

Color
Ivory

Grade
Commercial

Device Type
Duplex Receptacle

Strap Material
Steel

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

NEMA Configuration
5-20R

ELECTRICAL SPECIFICATIONS

Amperage
20 Ampere

Voltage
250 V AC

Poles
2

Termination 1
Side Wired, #12 AWG - #14
AWG Cu Solid or Stranded
wire

Termination 2

Grounding Capable
Grounding

Wires
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: CR20-IV

Box Qty : 10

Weight (Lbs) : 0.163

Carton Qty. : 100

IMS Code : 0289-0683

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM